

TECHNICAL DATA SHEET

SILICONE SPRAY LUBRICANT PART NO. 143543

PHYSICAL PROPERTIES

Chemical Type	Silicone
Appearance	Dries clear
Odor	Mild
Boiling/Cond. Point.....	-44°F to 290°F
Evaporation Rate	Slower than ether
NFPA Flammability Rating.....	2



DESCRIPTION

Dynatex® Silicone Spray Lubricant is a dry film lubricant which waterproofs, protects, reduces corrosion and lubricates. It is colorless, non-toxic, non-staining, non-corrosive and suitable for metal, plastic, rubber, vinyl, leather and wood.

FEATURES

- Lubricates to reduce friction and eliminate squeaks in all types of mechanical mechanisms
- Repels water
- Easy application, aerosol spray for maximum coverage, extension tube for hard to reach areas
- Prevents bonding, sticking and deterioration
- Test in accordance to 75/324/EEC Directive 6.1

TYPICAL APPLICATIONS

- Windshield wiper linkage
- Interior hinges, slides or springs
- Snow blower chutes
- Lubricates door locks, trunk lids, brake cables and rubber molding

DIRECTIONS FOR USE

1. Remove dirt and grease from surface being treated.
2. Provide adequate ventilation.
3. Shake can thoroughly before use. Note: There is no ball agitator inside the can. For best results, aerosol can should be at room temperature before spraying.
4. Holding can 8 to 10 inches from the surface for open area lubrication, or 5 inches using the extension tube provided for hard to reach areas, press the nozzle and discharge the product on the assembly.
5. Wipe excess with cloth.

GENERAL INFORMATION

Dynatex® Silicone Spray Lubricant is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.

Packaging

Colors: Clear

Size: 10.25 Oz Net Aerosol

STORAGE AND SHELF LIFE

Dynatex® Silicone Spray Lubricant should ideally be stored in a cool, dry location in unopened containers at a temperature between 46°F (8°C) to 82°F (28°C) unless otherwise labeled. DO NOT store within 1 meter (4 feet) of roofline of the warehouse of storage building. *Dynatex® Silicone Spray Lubricant* has a shelf life of 18 months from date of shipment

Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 120°F (50°C). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. **DO NOT SMOKE WHILE USING THIS PRODUCT.**

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non-warranty: Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.



350 Ring Road
Elizabethtown, KY 42701
Email: sales@dynatex.net
Website: www.dynatex.net

Toll Free: (800) 999-2937
Ph: (270) 769-5557
Fax (270) 769-6418